

# INSTRUCTIONS FOR USE

## FLASH PRO PREMIUM

### GUIDE INFORMATION FOR USE

#### MODEL: FLASH PRO PREMIUM long



#### MODEL: FLASH PRO PREMIUM short



#### FIREFIGHTER PROTECTIVE GLOVE ACCORDING TO EN 659:2003+A1:2008

- Palm, double-face knitted from 60% meta-aramid / 40% para-aramid with elastic, flame-resistant silicone coating (weight per unit area approx. 520 gr/m
- Back of the hand and cuff, fabric made of 50% Nomex® antistatic / 50% viscose FR, paris blue (approx. 275 gr/m<sup>2</sup>), with elastic, flame retardant Silicone coating (up to and including ankle protection)
- Eurotex-Insert as moisture barrier (PU membrane)
- Heat protection felt Needlona® made of 100% para-aramid as thermal insulation, Needlona KR122 in the palm of the hand (approx. 120 gr/m<sup>2</sup>), needle fleece of silica fibres (approx. 480 gr/m<sup>2</sup>) on the backhand and in the cuff
- Interlock knitted fabric /Para-Aramid as additional insulation Hand piece (approx. 200gr/m<sup>2</sup>)
- 70% Nomex gauntlet insulation® / 30% Viscose FR, grey melange, (approx. 175gr/m<sup>2</sup>)
- Shirred padding in the finger and ankle area, double-face knitted fabric made of 60% meta-aramid / 40% para-aramid
- 3M reflective stripes (yellow/silver/yellow) on the back of the gauntlet
- Reversible velcro fastener at the cuff entry

The protective gloves meet the requirements of the European PPE regulation (EU) 2016/425 and protect against risks that are covered by the standards on which the certification is based. Applied standards are EN 659:2003+A1:2008 (protective gloves for firefighters) and EN 420:2003+A1:2009

August Penkert GmbH  
Xantener Str. 12  
45479 Mülheim (Ruhr)  
Germany

Fon: 0208-41969-0  
Fax: 0208-41969-22  
E-Mail: mail@penkert.com  
Postcode 10 15 24

#### DESCRIPTION

The FLASH PRO PREMIUM is the logical development of the FLASH PRO - the protective glove for heavy-duty fire service work. Improved, additional padding in the thumb and finger area offers increased insulation properties to protect against radiant heat.

The new type of silicone coating on the palm and the back of the hand ensures a perfect grip. It is also flexible enough to ensure high mobility and allows the user to touch surfaces exceptionally well. The glove is washable at 60 degrees. The gloves are available in sizes 6 - 13.

#### APPLICATION

1. The gloves should be used according to its purpose.
2. Before every use, the gloves should be checked for possible damage.
3. Damaged gloves reduce the protective properties. The gloves should be kept clean.
4. Gloves that have become wet must not be dried by means of heating equipment.
5. Improper use of gloves can cause serious injuries or burns. In this case, the manufacturer assumes no responsibility.

As a user of the gloves, please observe the following instructions:

The gloves are only a part of the protective equipment for use. They protect the hands against heat and fire. However, they must not come into contact with open flames. At the same time, the gloves protect against mechanical risks such as abrasion, cuts, tearing and punctures.

In cases where there is a risk of getting caught in moving machine parts, gloves should not be worn.

#### TECHNICAL DATA

	REqUEST	RESULT
Abrasion resistance	3	3
Cut resistance	2	5
Tear resistance	3	4
Stitch Strength	3	3
Dexterity	1	3
TDM cut	A	D
Burning behaviour	4	4
Convective heat	min. 13.0s	23,9s palm
Radiant heat	min. 22.0s	22,7s
Contact heat, dry 250°	min. 10,0s	28,4s
Contact heat, wet 250°	min. 10,0s	25,2s
Heat shrinkage	<_5%	-0,3%
Seam strength	min. 350 N	458 N
Take off glove, dry	<_3s	1s
Take off glove, wet	<_3s	2s
Chemical Penetration	no penetration	pass



**August Penkert**  
Protective Gloves since 1967  
www.penkert.com

# INSTRUCTIONS FOR USE

# FLASH PRO PREMIUM

## GUIDE INFORMATION FOR USE

### CERTIFICATION

Notified certification body for personal protective equipment:  
(PSA): MIRTAKONTROL d.o.o.  
Gradiska 3-HR-10040 ZagrebDurava  
NB 2474  
Test report no.: OZO271-CPT005/20

### GLOVE SIZES

The glove sizes correspond to the application.  
The gloves cover the hand and, depending on the cuff length, parts of the forearm.

### STORAGE

Store in a ventilated room, preferably protected from light and dry

### LIABILITY

We accept no liability for damage caused by the non-targeted use of the PPE or by any use that does not comply 100% with the instructions for use given below. Please contact the manufacturer for further information regarding care instructions, repair and safe disposal methods.

### WASH INSTRUCTIONS



· according to washing expert opinion Lars Reuter (Master Textile Cleaner, Hamburg)  
alternative up to 60°C

### DECLARATION OF CONFORMITY

The declaration of conformity for this protective glove can be found at:  
[www.penkert.com](http://www.penkert.com)

August Penkert GmbH  
Xantener Str. 12  
45479 Mülheim (Ruhr)  
Germany

Fon: 0208-41969-0  
Fax: 0208-41969-22  
E-Mail: [mail@penkert.com](mailto:mail@penkert.com)  
Postcode 10 15 24

### CLEANING INSTRUCTIONS

Please take the following from the sewn-in identification label

### GENERAL INFORMATION

The results stated in the test report are based on laboratory tests carried out exclusively on unused gloves. Transferring the results to gloves after care treatment requires appropriate tests to be carried out.

The glove offers protection against puncturing with pointed objects in the sense of DIN EN 388:2016, but there is no protection against pointed objects such as injection needles.

The glove offers some protection against accidental contact with chemicals, but is not a protective glove against chemicals and microorganisms in the sense of DIN EN 374-1:2016+A1:2018.

We also point out that firefighter gloves should fit with the sleeves of the protective clothing so that the skin is not exposed when the arms are stretched out.

### CHECK

An optical check for dirt and damage is essential. Damaged gloves must be discarded. The expiration time depends on the degree of wear, use and area of application.

The clothing has a shelf life of at least 5 years from the date of manufacture. Non-compliance with the notes/regulations listed in this manual and individual stress during use may reduce the durability of PPE.

### PICTOGRAMS



EN 420:2003+A1:2009 EN 659:2003+A1:2008



**August Penkert**  
Protective Gloves since 1967  
[www.penkert.com](http://www.penkert.com)