INSTRUCTIONS FOR USE DEFENDER

GUIDE-INFORMATION FOR USE

MODEL: DEFENDER



|--|

CUT PROTECTIVE GLOVES ACCORDING TO EN 388:2016

- Palm: grain leather, approx. 1.0/1.1mm thick, Additional reinforcements incl. padding in the palm and palm area
- Sewn-on reinforcements in the palm of the hand
- Back of the hand: Spantex (93% polyester / 7% spandex), bright yellow Knuckle
- protection made of grain leather underlaid with approx. 5 mm thick foam padding - Fingertips made of rubberized material (silicone)
- Hand part completely reinforced with a high cut resistant inner glove
- Finger back with sewn-on protectors
- Leather ankle protection
- Neoprene cuff with pulse protection, velcro closure and eyelet
- Total length of glove approx. 27 cm
- Glove completely sewn with KEVLAR® brand fibre -pulse protection made of black grain leather
- Available in sizes 6 14
- EN 388:2016 (power levels 3344F)

The protective gloves meet the requirements of the European PPE Regulation (EU) 2016/425 and protect against mechanical and thermal risks (heat) covered by the standards on which the certification is based.

The applied standards are EN 388:2016 and EN 420:2003+A1:2009.

August Penkert GmbH Xantener Str. 12 45479 Mülheim (Ruhr) Germany

Fon: 0208-41969-0 Fax: 0208-41969-22 E-Mail: mail@penkert.com Postcode 10 15 24

DESCRIPTION

The TH protective gloves DEFENDER have been developed to protect your hands against mechanical risks - especially against cuts. The gloves are characterized by their excellent tactility (fingertip sensitivity). The DEFENDER meets the following requirements

The gloves do not contain any substances known to cause allergies. The materials used comply with the pH requirements of EN 420. The gloves are available in sizes 6 - 14.

APPLICATION

Observe the following points when wearing gloves: The glove does not protect against chemical and bacteriological hazards.

- In cases where there is a risk of moving machine parts getting caught, this protective glove must not be worn.
- Oil, grease and moisture reduce the cut resistance and increase the flammability of all gloves and should be avoided.
- The protective gloves are designed for work in a dry environment.

The expiration date (month and year) is indicated on the protective glove. (Example: 12.2026) It is not known that the performance levels according to EN388:2016 and EN 420:2003+A1:2009 change after up to 8 years of proper storage. Note: The production date is the printed expiration date minus 8 years.

TECHNICAL DATA

	RESULT
abrasion resistance	3
cut resistance	3
tear strength	4
puncture resistance	4
TDM: section	F

1= lowest power levels; 4 (5) = highest power level (A= weakest and F= highest power level linear cutting resistance); 0 = indicates that the glove falls below the minimum power level for the given single hazard. X = indicates that the glove has not been tested, or that the test procedure does not appear suitable / applicable. Note: If blunting occurs during the Coupe Cutting Strength Test, the results of the Coupe Test are for guidance only, whereas the TDM Cutting Strength Test provides reference performance results. Information on the performance level of the TDM test is binding for higher blunting of the cutting blade in the coupe test. In this case a Too high power level determined by blade truncation.

Even a high power level when determining the puncture resistance should not lead to the assumption of protection against puncture of a thin cannula.





INSTRUCTIONS FOR USE

GUIDE-INFORMATION FOR USE

CLEANING INSTRUCTION

MIRTAKONTROL d.o.o Gradiska 3 HR-10040 Zagreb Durava Croatia (NB): 2474 test report no: OZO271-CPT001/20

CARE AND REPAIR

CERTIFICATION

Dismantle gloves that are so badly damaged that they cannot be repaired and no longer offer protection.

The gloves which are so severely damaged and no longer provide protection must not be moved and the protective gloves used must be disposed of at an appropriate time depending on their use.

STORAGE

These gloves should be stored in their original packaging in a dry, clean place. Avoid exposing them to moisture or high temperatures.

LIABILITY

We do not accept any liability for damage caused by a non-targeted use of the PPE or by any use that does not comply 100% with the instructions for use below. Please contact the manufacturer for further information regarding care instructions, repair and safe disposal methods.

Please see the sewn-in identification label

GENERAL INFORMATION

The marking on the protective glove shows the essential protective performance characteristics and the contact to the responsible manufacturer. August Penkert GmbH Xanten Str.12 45479 Mülheim on the Ruhr Phone: 0208-41969-0 Fax: +49 208 41969 22 mail@penkert.com

WARNING

The degree of protection required for a particular task depends on the risks involved. You are ultimately responsible for selecting, using and operating the protective equipment that is appropriate to the risks at your workplace. Note that the protective performance may be adversely affected by application-related wear.

WASH INSTRUCTIONS

If you wash the gloves, please use a pH-neutral detergent.



according to washing report Lars Reuter (Textile Cleaner Master, Hamburg)

DECLARATION OF CONFORMITY

The declaration of conformity can be viewed at www.penkert.com

August Penkert GmbH Xantener Str. 12 45479 Mülheim (Ruhr) GERMANY Fon: 0208-41969-0 Fax: 0208-41969-22 E-Mail: mail@penkert.com Postcode 10 15 24

PICTOGRAMS

EN 420:2003+A1:2009







EN 388:2016

3344F



