

# INSTRUCTIONS FOR USE

## RINGERS R065T

### GUIDE-INFORMATION FOR USE

MODEL: RINGERS R065T



### DESCRIPTION

The protective glove RINGERS R065T is a breathable knitted glove, which is particularly suitable for technical assistance. The RINGERS R065T not only looks innovative, it is. In the palm a "sandy" nitrile coating provides the right grip, whether dry or wet. On the back of the hand and the fingers, flexible 3D protectors protect against knocks, blows and abrasion.

### APPLICATION

Observe the following points when wearing gloves: The glove does not protect against chemical and bacteriological hazards.

- In cases where there is a risk of moving machine parts getting caught, this protective glove must not be worn.
- Oil, grease and moisture reduce the cut resistance and increase the flammability of all gloves and should be avoided.
- The protective gloves are designed for work in a dry environment.

The expiration date (month and year) is indicated on the protective glove. (Example: 12.2026) It is not known that the performance levels according to EN388:2016 and EN 420:2003+A1:2009 change after up to 8 years of proper storage. Note: The production date is the printed expiration date minus 8 years.

### CUT PROTECTIVE GLOVES ACCORDING TO EN 388:2016

- Knit (polyester with steel fiber)
- Nitrile coating (sandy, red)
- 3D protectors (back of the hand and fingers)
- Touch screen capability (Smartphone etc.)
- High cut protection
- High puncture resistance
- Excellent grip in dry and wet conditions
- Knitted cuff (approx. 8 cm long)
- Total length approx. 27 cm (size 10)

The protective gloves meet the requirements of the European PPE Regulation (EU) 2016/425 and protect against mechanical and thermal risks (heat) covered by the standards on which the certification is based.

The applied standards are EN 388:2016 and EN 420:2003+A1:2009.

### TECHNICAL DATA

	RESULT
abrasion resistance	4
cut resistance	X
tear strength	4
puncture resistance	3
TDM: section	D
impact test (ankle protection)	P

1 = lowest power levels; 4 (5) = highest power level (A= weakest and F= highest power level linear cutting resistance); 0 = indicates that the glove falls below the minimum power level for the given single hazard. X = indicates that the glove has not been tested, or that the test procedure does not appear suitable / applicable.

**Note:** If blunting occurs during the Coupe Cutting Strength Test, the results of the Coupe Test are for guidance only, whereas the TDM Cutting Strength Test provides reference performance results.

Information on the performance level of the TDM test is binding for higher blunting of the cutting blade in the coupe test. In this case a Too high power level determined by blade truncation.

Even a high power level when determining the puncture resistance should not lead to the assumption of protection against puncture of a thin cannula.

# INSTRUCTIONS FOR USE

## RINGERS R065T

### GUIDE-INFORMATION FOR USE

#### CERTIFICATION

Certification body/testing institute :

CTC  
4, rue Hermann Frenkel  
69367 Lyon cedex 7 - France  
Notifizierte Stelle 0075  
Prüfbericht-Nr.: 0075/1256/162/07/18/1507

#### CLEANING INSTRUCTION

Please see the sewn-in identification label

#### CARE AND REPAIR

Protective gloves of the RINGERS R065T glove series must not be chemically cleaned, washed or treated with bleaching agents, gloves which are so severely damaged and no longer provide protection must not be re-used and the protective gloves used must be disposed of at an appropriate time depending on their use.

#### STORAGE


These gloves should be stored in their original packaging in a dry, clean place. Avoid exposing them to moisture or high temperatures.

#### LIABILITY

We do not accept any liability for damage caused by a non-targeted use of the PPE or by any use that does not comply 100% with the instructions for use below. Please contact the manufacturer for further information regarding care instructions, repair and safe disposal methods.

#### WASH INSTRUCTIONS

If you wash the gloves, please use a pH-neutral detergent.



optionally up to 60°C

- according to washing report  
Lars Reuter (Textile Cleaner Master, Hamburg)

#### GENERAL INFORMATION

The marking on the protective glove shows the essential protective performance characteristics and the contact to the responsible manufacturer.

August Penkert GmbH  
Xanten Str.12  
45479 Mülheim on the Ruhr  
Phone: 0208-41969-0  
Fax: +49 208 41969 22  
mail@penkert.com

#### WARNING

The degree of protection required for a particular task depends on the risks involved. You are ultimately responsible for selecting, using and operating the protective equipment that is appropriate to the risks at your workplace. Note that the protective performance may be adversely affected by application-related wear.

#### PICTOGRAMS

EN 420:2003+A1:2009



EN 388:2016



4X43DP



#### DECLARATION OF CONFORMITY

The declaration of conformity can be viewed at [www.penkert.com](http://www.penkert.com)

